



IGW1111/IGW1112-3IN1-DB

DIN-Rail Mounting

1/2 RS-232/485/422 + 2 100M Ethernet Ports Modbus Gateway

- Support 1/2 3IN1 DB9 serial port to 2 10/100Base-T(X) self-adaptive Ethernet interfaces
- Support conversion between Modbus RTU/ASCII and Modbus TCP protocol
- Support RTU Master, RTU Slave, ASCII Master, ASCII Slave and other operating modes
- Support virtual and real ID mapping to achieve flexible access between Master and Slave devices
- Support network modes such as redundant mode, switching mode and dual IP mode to meet the needs of various network environments
- Support 12~48VDC power supply input
- Support -40~75°C wide operating temperature range



Industrial Grade

Introduction

IGW1111/IGW1112-3IN1-DB Modbus gateway are designed for integrating Modbus RTU/ASCII and Modbus TCP; they can achieve the conversion between Modbus RTU/ASCII and Modbus TCP protocol. This series provide 2 types of products and support 1/2 3IN1 DB9 serial ports and 2 100M Ethernet copper port. They adopt DIN-rail mounting to meet the requirements of different application scenes.

Modbus gateway supports multiple network protocols, such as Modbus, TCP, IP, UDP, TELNET, ARP, ICMP, HTTP, HTTPS, SNMP, SSH, SMTP, SNTP, DNS and DHCP protocols. It possesses complete management function, and supports access control, rapid configuration, online upgrading, etc. RTU Master, RTU Slave, ASCII Master, ASCII Slave and other operating modes are supported; it supports up to 256 TCP client (master) accesses and connects up to 128 TCP server (slave) devices. TELNET, WEB and other access modes are also supported. It can provide users with good experience with friendly design of network management system interface, simple and convenient operation.

RESET button can achieve restore factory defaults. Hardware adopts fanless, low power consumption, wide temperature and voltage design and has passed rigorous industrial standard tests, which can suit for the industrial scene environment with harsh requirements for EMC. It can be widely used in PLC control and management, Building Automation System, Health Care Automation System, measuring instrument and environmental forces monitoring system.

Features and Benefits


- ⦿ Support 2 10/100Base-T(X) self-adaptive Ethernet interfaces and provide dual IP and MAC addresses to meet the requirements of multi-network management or network backups
- ⦿ Support 110bps-115200bps line speed and non-blocking communication
- ⦿ Support RTS/CTS, DTR/DSR and XON/XOFF flow control
- ⦿ Support response timeout setting of characters
- ⦿ Support RTU Master, RTU Slave, ASCII Master, ASCII Slave and other operating modes
- ⦿ Support up to 256 TCP client (master) accesses and connect up to 128 TCP server (slave) devices
- ⦿ Support virtual and real ID mapping to achieve flexible access between Master and Slave devices
- ⦿ Support IP address and MAC address filtering, which can achieve accurate access control easily
- ⦿ Support graded user management to implement humanized authority management
- ⦿ Support serial port status and parameters monitoring, ensuring the communication status be easy to read

- Support multiple configuration forms like Windows configuration tool, TELNET, SSHD and WEB
- File management is convenient for the device rapid configuration and online upgrading
- SSHD and HTTPS can guarantee the access security of data
- Conduct network diagnosis and troubleshooting via Ping and Traceroute
- Support multiple alarm methods, including e-mail alarm, log alarm and SNMP Trap alarm


Dimension

Unit: mm

- IGW1111-1DI-(3IN1)-DB-2P(12~48VDC)



- IGW1112-2DI-(3IN1)-DB-2P(12~48VDC)



Specification

Ethernet	Standard: 10Base-T, 100Base-TX Protocol: Modbus TCP, TCP, IP, UDP, ARP, HTTP, TELNET, SNMP, ICMP, DHCP, DNS Rate: 10/100M Automatic Flow Control, MDI/MDI-X Autotuning Interface quantity: 2 Interface form: RJ45
----------	---

	Duplex mode: Full/Half Duplex Mode Self-adaptive
Serial Port	<p>Standard: EIA RS-232C, RS-485, RS-422</p> <p>Protocol: Modbus RTU/ASCII</p> <p>Quantity of serial port: 1/2 3IN1 serial ports</p> <p>RS-232 signal: DSR, RTS, GND, TXD, RXD,CTS, DTR</p> <p>RS-485 signal: D+, D-, GND</p> <p>RS-422 signal: T+, T-, GND, R+, R-</p> <p>Baud rate: 110-115200bps</p> <p>Data bit: 7bit, 8bit</p> <p>Parity bit: None, Even, Odd, Space, Mark</p> <p>Stop bit: 1bit, 2bit</p> <p>Interface form: DB9</p> <p>Flow control: RTS/CTS, DTR/DSR, XON/XOFF</p> <p>Directional control: RS-485 direction adopts Automatic Data Direction Control technology</p> <p>Pull high/low resistor for RS-485: 4.7kΩ</p> <p>Electromagnetic isolation strength: 3KVDC/2KVrms</p> <p>Operating mode: RTU Master, RTU Slave, ASCII Master and ASCII Slave</p> <p>Connection quantity: support up to 256 TCP client (master) accesses and connect up to 128 TCP sever (slave) devices</p>
Configuration Method	WEB configuration management, TELNET configuration, Windows configuration tool, SSHD configuration
Security	User right classification, IP address filtering, MAC address filtering, SNMP/ Mail /System Log alarm, HTTP/HTTPS/SSHD/TELNET access control
Indicator	Power supply indicator, running indicator, Ethernet port indicator, serial port indicator
Power supply	<p>12~48VDC, 8-pin 5.08mm pitch terminal blocks, power supply occupies 4 pins in the left</p> <p>Power supply nonpolarity, dual power supply redundancy</p>
Power consumption	<p>No-load: 1.8W@12VDC</p> <p>Full-load: 1.9W@12VDC</p>
Working Environment	<p>Operating temperature: -40~75℃</p> <p>Storage temperature:-40~85℃</p> <p>Relative humidity: 5%~95% (no condensation)</p>
Physical Characteristic	<p>Housing: IP40 protection, metal</p> <p>Installation: DIN-Rail mounting</p> <p>Dimension (W x H x D): 33mm×138mm×110mm</p>

	Weight: 484g
--	--------------

IEC 61000-4-2 (ESD, electrostatic discharge), Level 3

- Air discharge: $\pm 8\text{kV}$
- Contact discharge: $\pm 6\text{kV}$

IEC 61000-4-4 (EFT, electrical fast transient pulses), Level 3

- Power supply: $\pm 2\text{kV}$
- Signal: $\pm 1\text{kV}$

Industrial Standard

IEC 61000-4-5 (Surge), Level 3

- Power supply: common mode $\pm 2\text{kV}$, differential mode $\pm 1\text{kV}$
- Signal: common mode $\pm 2\text{kV}$, differential mode $\pm 1\text{kV}$

Shock: IEC 60068-2-27

Free fall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Authentication	CE, FCC, RoHS
-----------------------	---------------

Warranty 3 years



Ordering Information

Available Models	100M copper port	3IN1 (RS-232/485/422)	Power supply
IGW1111-1DI-(3IN1)-DB-2P(12~48VDC)	2	1	12~48VDC dual power supply
IGW1112-2DI-(3IN1)-DB-2P(12~48VDC)	2	2	



Address: 3/B, Zone 1, Baiwangxin High Technology Industrial Park, Song Bai Road,
Nanshan District, Shenzhen, 518108, China

TEL.: +86-755-26702668 ext 835 FAX: +86-755-26703485

E-mail: ics@3onedata.com

Website: www.3onedata.com

◀ Please scan our QR code for more details

*Product pictures and technical data in this datasheet are only for reference. Updates are subject to change without prior notice. The final interpretation right is reserved by 3onedata.