



IMC-100

10/100Base-TX to 100Base-FX Fiber Converter



IMC-100 is an unmanaged industrial grade Fast Ethernet media converter that supports conversion between electrical 10/100Base-TX and optical 100Base-FX Ethernet. Simple DIP switch settings allow configuring the UTP port for auto-negotiation or for forced 10/100 speed and half/ full duplex as well as for enabling LFPT (Link Fault Pass Through), Ethernet flow control (802.3x) and selecting Switch Mode (store & forward) or Converter Mode (Jumbo frame Pass-through). Housed in rugged DIN rail or wall mountable enclosures, these converters are designed for harsh environments, such as industrial networking and intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications (See Figure).

Features

- Redundant dual DC input power 12/24/48VDC (9.6 ~ 58VDC)
- IP30 rugged metal housing and fanless
- Wide operating temperature -40 ~ 75°C (IMC-100-E)
- UL60950-1, CE, FCC, Rail traffic EN50121-4 certification
- Heavy industrial grade EMS, EMI, EN61000-6-2, EN61000-6-4 certified
- Store-and-Forward mode and Pass Through mode (set by DIP SW)
- Conversion between 10/100Base-TX and 100Base-FX cable interface
- Provides a DIP-Switch to set functions
- Supports LFPT (Link Fault Pass Through)

Specifications

| | |
|---------------------------------------|--|
| Standard | IEEE 802.3 10Base-T 10Mbit/s Ethernet IEEE 802.3u 100Base-TX, 100Base-FX, Fast Ethernet IEEE 802.3x Flow Control |
| RJ45 Ports | 10/100Base-TX Auto MDI/MDI-X and Auto-Negotiation Function Supports UTP CAT.5e Twisted Pair cable |
| Fiber Ports | 100Base-FX (SC/ST connectors) |
| Switch Architecture | Store and Forward in Switch mode Supports 1024 MAC addresses in Switch mode |
| Ethernet Packet length | 2046Byte (Max) in Switch mode |
| Jumbo Frame | 9K bytes in Pass through (Converter mode) |
| Fiber Parameters | Fiber Cable (Multi-mode): 50/125um, 62.5/125um Fiber Cable (Single-mode): 9/125um Wavelength: 1310nm (Multi-mode/Single-mode) Available distance: 2KM (Multi-mode) 30KM (Single-mode) 50KM (Single-mode) |
| Link Fault Pass Through (LFPT) | TX- Fiber: If TX port link down, the media converter will force Fiber port to link down Fiber-TX: If Fiber port link down, the media converter will force TX port to link down |
| DIP Switch | TP Auto Negotiation OFF: Auto Mode, ON: Force Mode Force TP Speed OFF: 100 Mbps, ON: 10 Mbps Force TP Duplex OFF: Full Duplex, ON: Half Duplex DIP Switch: ON: Enables LFPT (Link Fault Pass through) OFF: Disables LFPT (Link Fault Pass through) DIP Switch: ON: Flow Control Enable OFF: Flow Control Disable DIP Switch: OFF: Switching mode ON: Pass through Converter mode |
| Connector | Fiber: SC (Multi-mode, 2km), SC (Single-mode, 30km, 50KM) ST (Multi-mode, 2km), ST (Single-mode, 30km, 50KM) RJ-45 Socket: CAT.5e (10/100Mbps) Twisted Pair cable Auto MDI/MDI-X and Auto-Negotiation Function Support |
| LED | PWR 1 (Green): ON: Power1 active/ OFF: Power1 is inactive PWR 2 (Green): ON: Power2 active/ OFF: Power2 is inactive Fault (Red): ON: Fiber or TP has failed OFF: TP are functional Fiber (Green): ON : Connected to network OFF: Not connected to network/ BLK: Receive/Transmit Data |

| | |
|--|--|
| LED | 100 (Amber): ON: 100Mbps/ OFF: 10Mbps LAN (Green): ON : Connected to network OFF: Not connected to network/ BLK: Networking is active |
| Reverse Polarity Protection | Supported for power input |
| Overload Current Protection | Supported |
| Power Supply | 12/24/48VDC(9.6~58VDC), Redundant power with polarity reverse protect function and removable terminal block |
| Alarm Relay Contact | Relay outputs with current carrying capacity of 1 A @24VDC |
| Removable Terminal Block | Provides 2 redundant power, alarm relay contact |
| Power Consumption | 2.9 W |
| Operating Humidity | 5% ~ 95% (Non-condensing) |
| Operating Temperature | -40 ~ 75°C (IMC-100-E) |
| Storage Temperature | -40 ~ 85°C |
| Housing | Rugged Metal, IP30 Protection and fanless |
| Dimensions | 106 x 38.6 x 142.1mm (D X W X H) |
| Weight | 0.62kg |
| Installation | DIN Rail mounting, or wall mounting (Optional) |
| MTBF | 1,199,572 Hours MIL-HDBK-217 |
| Warranty | 5 years |
| Certification | |
| EMI | CE |
| EMI (Electromagnetic Interference) | FCC Part 15 Subpart B Class A, CE |
| Railway Traffic | EN50121-4 |
| Immunity for Heavy Industrial Environment | EN61000-6-2 |

| | |
|---|---|
| EMS | EN61000-4-5 (Surge) Level 3, Criteria B |
| (Electromagnetic Susceptibility) | EN61000-4-6 (CS) Level 3, Criteria A |
| Protection Level | EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A |
| Safety | UL60950-1 |
| Shock | IEC 60068-2-27 |
| Freefall | IEC 60068-2-32 |
| Vibration | IEC 60068-2-6 |

Figure : IMC-100 Media Converter Transmission



Industrial Unmanaged FE Converter



Front View

Rear View

DIN-Rail Kit View



| Temperature | Connector Type | Connectivity Distance |
|----------------|-------------------------------|-----------------------|
| -40°C ~ +85°C | Standard Connector | ≤ 10m |
| -40°C ~ +125°C | High Temperature Connector | ≤ 10m |
| -40°C ~ +175°C | Extreme Temperature Connector | ≤ 10m |

IMC-100 – □ – □□□□□□
Example: IMC-100 – E – SC002

- ## Optional Accessories

| | |
|-----------|---|
| IND-WMK01 | Wall Mount kit for Industrial product, 184 x 30mm |
|-----------|---|