

ES5010G-2GS-8POE-150W-P(220VAC) 10*10/100/1000M Base-T PORTS POE SWITCH

Features

1. Compatible with both IEEE802.3at(30W) and IEEE802.3af(15.4W), can supply power to PDs under these two standards
2. Automatically detect and supply power to IEEE802.3at and IEEE 802.3af compliant powered devices(PDs)
3. Advanced SAFC function, only supply power to IEEE 802.3af/at compliant PDs, no worry about damaging other private standard POE devices or devices without POE function
4. Support port power supply prioritization, guarantee the continuous power supply of key nodes
5. Up to 100m network cable transmitting distance
6. Built-in PSE power supply module, plug-and play design, easy to install
7. High security performance defending against power surge
8. Support short-circuit protection function
9. Energy-saving green design, support auto-switch to standby mode and auto-detect cable length.
10. Support simple WEB management, easy to configure the functions of switches



Introduction

ES5010G-2GS-8POE-150W-P(220VAC) is Full gigabit , managed , 8-port Gigabit high power (IEEE 802.3at) PoE Switch,utilizing a compact factor which can be mounted in a 19-inch rack with rack-mounting kits or placed on desktop.

With data and power supported by one unit, the

ES5010G-2GS-8POE-150W-P(220VAC) shall reduce cables and eliminate the need for dedicated electrical outlets on the wall,ceiling or any unreachable place. Auto PoE detection and Plug and play installation makes P3000M series Gigabit PoE Switch easy to use and with clear LED indicators to tell the working condition.

Specification

Technology:

Standard and Protocols: IEEE 802.3af, Power Over Ethernet, IEEE 802.3at, Power Over Ethernet Plus

IEEE 802.3u, 100BASE-TX, IEEE 802.3ab, 1000 BASE-T, IEEE 802.3z, 1000 BASE-X, IEEE 802.3ad, Static or Dynamic Link Aggregation, IEEE 802.3x, Full-Duplex Flow Control, IEEE 802.3az, EEE(Energy Efficient Ethernet), IEEE 802.1q, VLAN IEEE 802.1p, QoS/CoS, IEEE 802.1d, STP(Spanning Tree Protocol), IEEE 802.1w, Rapid Spanning Tree Protocol, IEEE 802.1s, Multiple Spanning Tree Protocol

POE Standard: IEEE802.3af/at

Flow control: Back-pressure traffic control under Half-Duplex mode, IEEE 802.3x traffic control under Full-Duplex mode

Ports:

Fixed ports: 8*10/100/1000M PoE ports+2* Gigabit SFP ports

PoE Pin-out: 1/2(+), 3/6(-); Customized 4/5(+),7/8(-)

Exchange Properties:

100M forwarding rate: 1488095pps

100M forwarding rate: 148809pps

10M forwarding rate: 14880pps

Transmit type: Full wire-speed storage and forwarding

MAC address: 8K, Support auto-update, two-way learning

VLAN: Port-based VLANs\ Port-protocol-based VLANs \ ACL-based VLANs, 4K-entry Vlan Table, Supports flexible Q-in-Q and Vlan Tag function, VLANs based on IEEE 802.1q

Switching Capacity: ≥9.2Gbps

Spanning Tree: Spanning Tree Protocol, Rapid

Spanning Tree Protocol(RSTP),

Support Multiple Spanning Tree

Protocol

Link Aggregation:Support 8 aggregation groups, and a maximum of 8 ports in each aggregation group

Port Mirroring: Support bi-direction port mirroring, RSPAN function for remote mirroring

Port Isolation: Isolation between downlink ports without influence the communication between downlink and uplink ports

Port Flow Control:Back-pressure traffic control under Half-Duplex mode,IEEE 802.3x traffic control under Full-Duplex mode

Port Rate Restriction: Port-based ingress or egress rate limiting

Storm Suppression: Support the suppression of broadcast storm based on forwarding rate

Multicast Control: Support IGMPv1/2/3 and MLDv1/2 Snooping;

Security: 1.5K entry ACL Table,

Attack Prevention(Land attack\Blat attack\Ping attack\TCP control flag attack), MAC & Port based Security, 802.1x port based security, TCP/UDP port based Security

QOS:SP (Strict Priority), WFQ (Weighted Fair Queuing), WRR (Weighted Round Robin), 802.1p(Port Queuing Priority), Differentiated Service Code Point(DSCP Priority)

IPv6:IPv6 Parsing

PoE ouput priority Management: Supported

Physic Medium:

10/100Base-TX: UTP category 3/4/5 cables(Maximum 100m)

1000Base-T: UTP Category 5 cable(Maximum 100m)

1000Base-SX: fiber with 850nm wavelength, supports a max transmission distance of 550m

1000Base-LX: fiber with 1310nm / 1550nm wavelength, supports a max transmission distance of 80km

Network Cable Deployment:Support Auto-MDIX function, automatically identify straight forward cable and cross-over cable

Negotiation Pattern: Support port auto-negotiation function(automatically negotiate transmission rate and Duplex modes)

PHY Detection: Detect the connectivity of network cables

Maintenance: Detect the connectivity of network cables,Uploading or downloading of the configuration data, Uploading of upgrade patch, Support system logs,

WEB-based reset to factory defaults

Management: Support WEB-based management

Indicator light:

Interface light: Link/Act, POE Status

Power light: PWR

Power:

Input Power Supply: 90~264VAC/50~60Hz/150W

Energy Saving:Comply with “EEE” Energy Efficient Ethernet

Working Environment:

Working Temperature: -20~50°C

Storage Temperature: -40~70°C

Operation Humidity:10%~90%(non-condensing)

Storage Humidity:5%~95%(non-condensing)

Mechanical Properties:

Weight: <2Kg

Dimensions (L×W×H) :280×180×44mm

Warranty:

Warranty time: 5 years

Dimension

