

# ADAM-5060

# ADAM-5069

## 6-ch Relay Output Module

## 8-ch Power Relay Output Module with LED



ADAM-5060



### Specifications

#### General

- Certification CE
- Connectors 1 x Plug-in screw terminal (# 14 ~ 22 AWG)
- Enclosure ABS+PC
- Power Consumption 1.8 W (max.)

#### Relay Output

- Breakdown Voltage 500 V<sub>AC</sub> (50/60 Hz)
- Channels 2 x form A, 4 x form C
- Contact Rating AC: 125 V @ 0.6 A  
250 V @ 0.3 A  
DC: 30 V @ 2 A  
110 V @ 0.6 A
- Insulation Resistance 1 GΩ min. @ 500 V<sub>DC</sub>
- Relay Off Time (typical) 2 ms
- Relay On Time (typical) 3 ms
- Total Switching Time 10 ms

### Ordering Information

- ADAM-5060 6-ch Relay Output Module



ADAM-5069



### Specifications

#### General

- Certification CE, FCC class A
- Connectors 1 x Plug-in screw terminal (# 14 ~ 22 AWG)
- Enclosure ABS+PC
- LED Indicator On: Active  
Off: Inactive
- Power Consumption 2.2 W (max.)

#### Relay Output

- Breakdown Voltage 750 V<sub>AC</sub> (50/60 Hz)
- Channels 8 x form A
- Contact Rating AC: 250 V @ 5 A  
DC: 30 V @ 5 A
- Insulation Resistance 1 GΩ @ 500 V<sub>DC</sub>
- Relay On Time (typical) 5 ms
- Relay Off Time (typical) 5.6 ms

### Ordering Information

- ADAM-5069 8-ch Power Relay Output Module w/ LED