

ADAM-5060

ADAM-5069

6-ch Relay Output Module

8-ch Power Relay Output Module with LED



ADAM-5060



Specifications

General

- Certification CE
- Connectors 1 x Plug-in screw terminal (# 14 ~ 22 AWG)
- Enclosure ABS+PC
- Power Consumption 1.8 W (max.)

Relay Output

- Breakdown Voltage 500 V_{AC} (50/60 Hz)
- Channels 2 x form A, 4 x form C
- Contact Rating AC: 125 V @ 0.6 A
250 V @ 0.3 A
DC: 30 V @ 2 A
110 V @ 0.6 A
- Insulation Resistance 1 GΩ min. @ 500 V_{DC}
- Relay Off Time (typical) 2 ms
- Relay On Time (typical) 3 ms
- Total Switching Time 10 ms

Ordering Information

- ADAM-5060 6-ch Relay Output Module



ADAM-5069



Specifications

General

- Certification CE, FCC class A
- Connectors 1 x Plug-in screw terminal (# 14 ~ 22 AWG)
- Enclosure ABS+PC
- LED Indicator On: Active
Off: Inactive
- Power Consumption 2.2 W (max.)

Relay Output

- Breakdown Voltage 750 V_{AC} (50/60 Hz)
- Channels 8 x form A
- Contact Rating AC: 250 V @ 5 A
DC: 30 V @ 5 A
- Insulation Resistance 1 GΩ @ 500 V_{DC}
- Relay On Time (typical) 5 ms
- Relay Off Time (typical) 5.6 ms

Ordering Information

- ADAM-5069 8-ch Power Relay Output Module w/ LED