

ADAM-3613-AE

ADAM-3618-AE

4-ch RTD Input Module

4-ch Thermocouple Input Module

NEW



ADAM-3613-AE



CE FCC

Specifications

General

- Power Consumption 1W(Max)
- Certification CE/FCC

Analog Input

- Channels 4, 3-wired
- Input Impedance >1M Ω
- Input Type Pt, Balco and Ni RTD
- Temperature Range

Pt 100	-50°C ~ 150°C
	0°C ~ 100°C
	0°C ~ 200°C
	0°C ~ 400°C
	-200°C ~ 200°C

Supports both IEC 60751 ITS90 (0.03851 W/W/°C) and JIS C 1604 (0.03916 W/W/°C)

Pt 1000	-40°C ~ 160°C
Balco 500	-30°C ~ 120°C
Ni 518	-80°C ~ 100°C
	0°C ~ 100°C

- Resolution 16-bit with accuracy 0.1% of Full Scale Range
- Sampling Rate 10 sample/second (total)
- Accuracy $\pm 0.1\%$ of Full Scale Range
- CMR @ 50/60 Hz 90dBs
- NMR @ 50/60 Hz 60dBs
- Span Drift ± 25 ppm/°C
- Zero Drift $\pm 6\mu V/^\circ C$
- Isolation Voltage 2000 V_{DC}
- Burn-out detection Yes

Environment

- Operating Temp. -40 ~ 70 °C
- Storage Temp. -40 ~ 85 °C
- Humidity 5~95% (no-condensation)

Ordering Information

- ADAM-3613-AE 4-ch RTD Input Module

NEW



ADAM-3618-AE



CE FCC

Specifications

General

- Power Consumption 1W (Max)
- Certification CE/FCC

Analog Input

- Channels 4
- Input Type J, K, T, E, R, S, B Type Thermocouple
- Temperature Range

Type J	(0 ~ 760°C)
Type K	(0 ~ 1370°C)
Type T	(-100 ~ 400°C)
Type E	(0 ~ 1000°C)
Type R	(500 ~ 1750°C)
Type S	(500 ~ 1750°C)
Type B	(500 ~ 1800°C)

- Resolution 16-bit
- Sampling rate 10 sample/second (total)
- Input Impedance >1 M Ω
- Accuracy $\pm 3^\circ C$
- CMR @ 50/60 Hz 90 dBs
- NMR @ 50/60 Hz 60 dBs
- Span Drift 0.0055%
- Zero Drift $\pm 6\mu V/^\circ C$
- Isolation Voltage 2000 V_{DC}
- Burn-out detection Yes

Environment

- Operating Temp. -40 ~ 70°C
- Storage Temp. -40 ~ 85°C
- Humidity 5 ~ 95% (no-condensation)

Ordering Information

- ADAM-3618-AE 4-ch Thermocouple Input Module