



IES318 Series

DIN-Rail or Wall Mounting

8-port 100M Layer 2 Unmanaged Industrial Ethernet Switch

- Support 4 100M Ethernet copper ports and 4 100M Ethernet ports (optional fiber/copper ports)
- Support relay alarm output
- Support 9~60VDC dual power input and power supply nonpolarity
- Support 220VAC/DC power supply input
- Support -40~75°C wide temperature operation



Industrial Grade

Fanless Design

RPS

Introduction


IES318 series is an 8-port 100M layer 2 unmanaged industrial Ethernet switch. This series provides 8 products and supports 100M copper ports and 100M fiber ports. They adopt wall or DIN-Rail mounting to meet the requirements of different application scenes.

DC power supply input consists of two independent power supply circuits, which can ensure device's normal operation when one fails. The design of DIP switch can realize port alarm and power alarm. When power supply or port has link failure, ALARM indicator will be bright and send out alarm, meanwhile, alarm device connected to the relay will send out alarm for rapid scene troubleshooting. Hardware adopts fanless, low power consumption, wide temperature and voltage design and has passed rigorous industrial standard tests, which can suit for the industrial scene environment with harsh requirements for EMC. It can be widely used in smart grid, rail transit, smart city, safety city, new energy, intelligent manufacturing and other industrial fields.


Dimension

Unit: mm


● IES318-4T4F-2P48




● IES318-4T4F-P220




● IES318-6T2F-2P48




● IES318-6T2F-P220




● IES318-7T1F-2P48




● IES318-7T1F-P220



● IES318-8T-2P48



● IES318-8T-P220



Specification

Standard & Protocol

IEEE 802.3 for 10Base-T
IEEE 802.3u for 100Base-TX and 100Base-X

Interface

Copper port: 10/100Base-T(X), RJ45, Automatic Flow Control, Full/Half Duplex Mode Self-Adaption, MDI/ MDI-X Autotuning
Fiber port: 100Base-X, optional SC/ST/FC

Alarm port: 2-pin 7.62mm pitch terminal blocks, supports 1 relay alarm output, and the current load capacity is 1A@24VDC or 0.5A@120VAC

Indicator	Running Indicator, Port Indicator, Power Supply Indicator, Alarm Indicator																													
Switching Property	Transmission mode: store and forward MAC address: 2K Buffer: 1Mbit Backplane bandwidth: 1.6G Switch time delay: <10μs																													
Power Supply	<ul style="list-style-type: none">DC power: 12/24/48VDC (9~60VDC), with dual power supplies, built-in overcurrent protection, supports nonpolarityAC power: 220 VAC/DC (85~264VAC/DC), with built-in overcurrent protection																													
Power Consumption	<table><tr><th>Model</th><th>No-load</th><th>Full-load</th></tr><tr><td>IES318-4T4F-2P48</td><td>3.8W@48VDC</td><td>4.3W@48VDC</td></tr><tr><td>IES318-4T4F-P220</td><td>4.2W@220.6VAC</td><td>4.7W@221VAC</td></tr><tr><td>IES318-6T2F-2P48</td><td>2.2W@48VDC</td><td>3.0W@48VDC</td></tr><tr><td>IES318-6T2F-P220</td><td>2.6W@220.4VAC</td><td>3.3W@220VAC</td></tr><tr><td>IES318-7T1F-2P48</td><td>0.9W@48VDC</td><td>1.9W@48VDC</td></tr><tr><td>IES318-7T1F-P220</td><td>2.1W@220VAC</td><td>2.8W@220VAC</td></tr><tr><td>IES318-8T-2P48</td><td>0.9W@48VDC</td><td>1.9W@48VDC</td></tr><tr><td>IES318-8T-P220</td><td>1.2W@220VAC</td><td>2.0W@220VAC</td></tr></table>			Model	No-load	Full-load	IES318-4T4F-2P48	3.8W@48VDC	4.3W@48VDC	IES318-4T4F-P220	4.2W@220.6VAC	4.7W@221VAC	IES318-6T2F-2P48	2.2W@48VDC	3.0W@48VDC	IES318-6T2F-P220	2.6W@220.4VAC	3.3W@220VAC	IES318-7T1F-2P48	0.9W@48VDC	1.9W@48VDC	IES318-7T1F-P220	2.1W@220VAC	2.8W@220VAC	IES318-8T-2P48	0.9W@48VDC	1.9W@48VDC	IES318-8T-P220	1.2W@220VAC	2.0W@220VAC
Model	No-load	Full-load																												
IES318-4T4F-2P48	3.8W@48VDC	4.3W@48VDC																												
IES318-4T4F-P220	4.2W@220.6VAC	4.7W@221VAC																												
IES318-6T2F-2P48	2.2W@48VDC	3.0W@48VDC																												
IES318-6T2F-P220	2.6W@220.4VAC	3.3W@220VAC																												
IES318-7T1F-2P48	0.9W@48VDC	1.9W@48VDC																												
IES318-7T1F-P220	2.1W@220VAC	2.8W@220VAC																												
IES318-8T-2P48	0.9W@48VDC	1.9W@48VDC																												
IES318-8T-P220	1.2W@220VAC	2.0W@220VAC																												
Working Environment	Operating temperature: -40~75℃ Storage temperature:-40~85℃ Relative humidity: 5%~95% (no condensation)																													
Physical Characteristic	Housing: IP40 protection, high-strength corrugated metal Installation: DIN-Rail or wall mounting Dimension (W x H x D): 53mm×138mm×110mm Weight: 670g																													
AC Product Industrial Standard	<p>IEC 61000-4-2 (ESD), Level 3</p> <ul style="list-style-type: none">Air discharge: ±8kVContact discharge: ±6kV <p>IEC 61000-4-4 (EFT),Level3</p> <ul style="list-style-type: none">Power supply: ±2kVEthernet port: ±1kVRelay: ±2kV																													

	<p>IEC 61000-4-5 (Surge), Level 3</p> <ul style="list-style-type: none">● Power supply: common mode $\pm 2\text{kV}$, differential mode $\pm 1\text{kV}$● Ethernet port: common mode $\pm 2\text{kV}$, differential mode $\pm 1\text{kV}$● Relay: common mode $\pm 2\text{kV}$, differential mode $\pm 1\text{kV}$ <p>Shock: IEC 60068-2-27 Free fall: IEC 60068-2-32 Vibration: IEC 60068-2-6</p>
DC Product Industrial Standard	<p>IEC 61000-4-2 (ESD), Level 4</p> <ul style="list-style-type: none">● Air discharge: $\pm 15\text{kV}$● Contact discharge: $\pm 8\text{kV}$
	<p>IEC 61000-4-4 (EFT), Level 4</p> <ul style="list-style-type: none">● Power supply: $\pm 4\text{kV}$● Ethernet port: $\pm 2\text{kV}$● Relay: $\pm 4\text{kV}$
	<p>IEC 61000-4-5 (Surge), Level 4</p> <ul style="list-style-type: none">● Power supply: common mode $\pm 4\text{kV}$, differential mode $\pm 2\text{kV}$● Ethernet port: common mode $\pm 4\text{kV}$, differential mode $\pm 2\text{kV}$● Relay: common mode $\pm 4\text{kV}$, differential mode $\pm 2\text{kV}$ <p>Shock: IEC 60068-2-27 Free fall: IEC 60068-2-32 Vibration: IEC 60068-2-6</p>
Authentication	CE, FCC, RoHS
Warranty	5 years

Ordering Information

Model	100M Copper Port	100M Fiber Port	Power Supply
IES318-4T4F-2P48	4	4	12/24/48VDC (9~60VDC) dual power supply
IES318-4T4F-P220	4	4	220VAC/DC (85~264VAC/DC)
IES318-6T2F-2P48	6	2	12/24/48VDC (9~60VDC) dual power supply
IES318-6T2F-P220	6	2	220VAC/DC (85~264VAC/DC)
IES318-7T1F-2P48	7	1	12/24/48VDC (9~60VDC) dual power supply
IES318-7T1F-P220	7	1	220VAC/DC (85~264VAC/DC)
IES318-8T-2P48	8	—	12/24/48VDC (9~60VDC) dual power supply
IES318-8T-P220	8	—	220VAC/DC (85~264VAC/DC)



Address: 3/B, Zone 1, Baiwangxin High Technology Industrial Park, Song Bai Road,
Nanshan District, Shenzhen, 518108, China

TEL.: +86-755-26702668 ext 835

FAX: +86-755-26703485

E-mail: ics@3onedata.com

Website: www.3onedata.com

◀ Please scan our QR code for more details

*Product pictures and technical data in this datasheet are only for reference. Updates are subject to change without prior notice. The final interpretation right is reserved by 3onedata.