

MAS-5282-EG

8-Axis Extended-Type Motion Controller

NEW



Features

- Motion Studio: Rapid application development tool
- Programmable with BASIC language
- 8-axis motion controller with 32-ch digital I/O
- RS-232 and TCP/IP support
- Quick configuration user interface
- Programmable encryption to protect intellectual property
- Built-in quick programming assistant
- C-integration: External DLL interface
- 2/3-axis linear, 2/3-axis circular, and helical interpolation
- 2-axis position comparison trigger, high-speed latch

Introduction

The MAS-5282-EG is a PC-based Programmable motion controller based on the Motion Studio software development tool. It features a range of built-in debugging tools and can be programmed using BASIC programming language. The unit is suitable for various applications and can greatly shorten the equipment development cycle.

The MAS-5282-EG is integrated with a high-performance digital signal processor and field-programmable gate array. It can easily calculate trajectories, perform real-time motion control, and provide I/O processing support functions such as linear, circular, and helical interpolation. Other features include a multiaxis comparison trigger, high-speed position latch, and T/S-curve acceleration/deceleration support. Additionally, with Motion Studio, users can easily complete system configuration and diagnosis, enabling the simple and fast realization of complex motion control functions.

Specifications

General

- **Dimensions (W x H x D)** 232 x 90 x 232 mm (9.13" x 3.54" x 9.13")
- **Power Requirements** 100 ~ 240 V_{AC}
- **Weight** 5 kg
- **OS** Win7 Embedded x86/x64

System Hardware

- **CPU** 4th Generation Intel® Core™ i3 (LGA1150)
- **Memory** 4GB DDR3
- **Storage** 500GB

I/O Interface

- **Serial Ports** 2 x RS-232
- **LAN** 2 x 10/100/1000M (RJ45)
- **USB Ports** 4 x USB 2.0
- **PCI Express** 1 x PCIe x4

Motion Control

- **Number of Axes** 8
- **Interpolation** 2/3-axis linear, 2/3-axis circular, and helical
- **Comparison Trigger** 2/3-axis position
- **High-Speed Latch** 8-ch
- **Handwheel/JOG** 8-ch
- **Max. Output Speed** 5 Mpps
- **Pulse Output Type** CW/CCW or pulse/direction
- **Encoder Interface** 8-ch, quadrature (A/B phase) or up/down
- **Velocity Profiles** T/S-curve
- **Local I/O** LMT+, LMT-, ORG, ALM, INP, CMP, LTC
- **General Inputs** 32
- **General Outputs** 32

Supports I/O Expansion Cards

- **PCIE-1730-AE** 16-ch isolated digital I/O card
- **PCIE-1756-AE** 32-ch isolated digital I/O card

Motion Studio Software Development Tool

- **Programming Language** MAS BASIC
- **Number of Tasks** Up to 10 tasks can be executed independently or simultaneously
- **Communication Protocols** Modbus RTU/TCP, RS232, RS485, and TCP/IP
- **Debugging Tools** Terminal, watch, I/O Viewer, motion test tool, parameter viewer, VR viewer breakpoint operation, single step debugging, C-integration
- **Other Functions** Programmable encryption, virtual controller, programming assistant, remote monitoring and diagnosis

Ordering Information

- **MAS-5282-EG50003** 8-axis extended-type motion controller with 32-ch digital I/O

Accessories

- **PCL-101100SB-1E/2E/3E** 100-pin mini SCSI cable, 1/2/3 m
- **ADAM-3956-AE** 100-pin DIN rail SCSI 4-axis motion wiring board
- **PCL-10153PA5-2E** 50-pin cable to Panasonic A4/A5 servo, 2 m
- **PCL-10153YS5-2E** 50-pin cable to Yaskawa Sigma V/7 servo, 2 m
- **PCL-10153MJ3-2E** 50-pin cable to Mitsubishi J3/J4 servo, 2 m
- **PCL-10153DA2-2E** 50-pin cable to Delta A2 servo, 2 m
- **96PD-S1P0-SYSE** License for WebAccess/HMI Runtime with 500 tags
- **PCIE-1730-AE** 16-ch isolated digital I/O card
- **PCIE-1756-AE** 32-ch isolated digital I/O card