

Zlinx® Xtreme Wireless I/O

IP67 Industrial Outdoor Rated

Models BB-ZXT9-IO-222R2-A, BB-ZXT24-IO-222R2

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Wire replacement for serial communications - cable-free, license-free
- Baud: 250 kbps (2.4 GHz, short range); 9.6 or 115.2 S/W selectable (900 MHz, long-range, North America only)
- Wide operating temperature range: -40 to +74 °C
- IP67, industrial heavy-duty, DIN rail mount enclosure
- Wide range power input: 10-30 VDC (power supply required, not included, sold separately)
- Flexible configuration for multiple types of analog/digital I/Os
- Signal Strength Indicator (SSI), AES encryption, Modbus compatible
- UL C1/D2; CE (2.4 GHz only)

Do you need to monitor remote assets via discrete analog and digital sensors or control remote control equipment from a central SCADA/PLC? Is your remote equipment outdoors? Zlinx Xtreme I/Os can do the job faster, easier and more economically than running cable.

These compact and rugged IP67 units are ideal for outdoor applications and extreme weather conditions for connecting remote I/Os to local I/Os wirelessly (via peer-to-peer mode) or to connect remote I/Os in multiple locations to a central PLC/SCADA/HMI system via a serial radio modem (via Modbus mode).

Zlinx industrial wireless I/O products operate in license-free, proprietary RF 900 MHz and 2.4 GHz ISM bands. Select the 900 MHz version for longer distances (North America only). For further flexibility, the output power is software selectable. The 900 MHz unit offers 256-bit AES encryption. The 2.4 GHz has 128-bit AES encryption.

Zlinx wireless I/O products support 10 to 30 VDC wide range input power. An external power source is required (not included, sold separately).

A starter kit, Model BB-ZXT9-IOA-KIT, conveniently bundles two 900 MHz IO units, two power supplies and a USB programming cable to set up your application. (North America only.)

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION	ANALOG INPUTS	ANALOG OUTPUTS	DIGITAL INPUTS	DIGITAL RELAY OUTPUTS
Zlinx Xtreme Wireless I/O					
BB-ZXT9-IO-222R2-A	900 MHz*	2	2	2	2
BB-ZXT24-IO-222R2	2.4 GHz*	2	2	2	2

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
900 MHz Zlinx Xtreme Wireless I/O Kit *	
BB-ZXT9-IOA-KIT*	Zlinx Xtreme IP67 Peer-to-Peer I/O Kit: 2 - BB-ZXT9-IO-222R2-A (I/O modules) 2 - BB-CLG-60-24 (power supply) 1 - BB-USBAMB-6F (programming cable)

* 900 MHz for North America only.

Check with your local distributor for availability and options.

Check wireless regulations/standards in your geographic area.

ACCESSORIES - sold separately

BB-CLG-60-24	IP67 Power Supply, 24VDC, 60W, Panel Mount
BB-ZXT9-ANT	900 MHz Spare Antenna
BB-ZZ24D-ANT1	2.4 GHz Spare Antenna
BB-ZXTMT	Conduit Mounting Kit

All product specifications are subject to change without notice.

BB-ZXTx-IO222R2_ZlinxXtremeIO_4918ds

B+B SMARTWORX

Powered by

ADVANTECH

orders@advantech-bb.com
support@advantech-bb.com

Corporate Headquarters: 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park, Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445

Zlinx® Xtreme Wireless I/O

IP67 Industrial Outdoor Rated

Models BB-ZXT9-IO-222R2-A, BB-ZXT24-IO-222R2



SPECIFICATIONS

RF PROPERTIES	
Physical Standard	802.15.4
FREQUENCY	
BB-ZXT9-IO-222R2-A	900 MHz ISM (902 – 928 MHz)
BB-ZXT24-IO-222R2	2.4 GHz ISM (2.4 – 2.5 GHz)
TRANSMIT POWER	
BB-ZXT9-IO-222R2-A (NATAM only)	1 mW, 10 mW, 100 mW, 500 mW 1 W – software selectable
BB-ZXT24-IO-222R2	10 mW, 16 mW, 25 mW, 30 mW 63 mW – software selectable
RECEIVER SENSITIVITY	
BB-ZXT9-IO-222R2-A	-100 dBm
BB-ZXT24-IO-222R2	-105 dBm
OVER THE AIR DATA RATE	
BB-ZXT9-IO-222R2-A	9.6 or 115.2 kbps, software selectable
BB-ZXT24-IO-222R2	250 kbps
OUTDOOR RANGE*	
BB-ZXT9-IO-222R2-A	Supplied Antenna – 23 km (14 mi) High Gain Antenna – 64 km (40 mi)
BB-ZXT24-IO-222R2	Supplied Antenna – 2.4 km (1.5 mi) High Gain Antenna – 6 km (10 mi)
*Range estimates based on optimal RF conditions and an unobstructed line of sight.	
TRANSMISSION METHOD	
BB-ZXT9-IO-222R2-A	FHSS
BB-ZXT24-IO-222R2	DSSS
Modulation	FSK
CHANNEL CAPACITY	
BB-ZXT9-IO-222R2-A	10 hop sequences share 50 frequencies
BB-ZXT24-IO-222R2	12 direct sequence channels
Network Topologies	I/O to I/O: one-to-one (peer-to-peer mode) Radio Modem to I/O: one-to-many (Modbus I/O mode)
ENCRYPTION	
BB-ZXT9-IO-222R2-A	256-bit AES
BB-ZXT24-IO-222R2	128-bit AES
SUPPLIED ANTENNA	
BB-ZXT9-IO-222R2-A	Impedance – 50 Ω Connector – RPSMA female VSWR – 2.0 maximum (in-band) Gain – 3 dBi Polarization – vertical Length – 198 mm (7.8 in)
BB-ZXT24-IO-222R2	Impedance – 50Ω Connector – RPSMA female VSWR – 2.0 maximum (in-band) Gain – 2.1 dBi Polarization – vertical Length – 113 mm (4.38 in)
Antenna Connection	RPSMA male
CONTROLS AND INDICATORS	
Signal Strength	8 Green RSSI LEDs indicate signal strength
Power	Green LED
Receive Data	Green LED
Transmit Data	Green LED
Programming Port	USB
Reset	Push Button
OPERATING SYSTEM	
O/S	Windows XP, 7, 8, 8.1, 10
POWER	
External Source	Power supply required (not included, sold separately)
Power Connector	Terminal Block
Input Voltage	10 – 30 VDC
Power Use	BB-ZXT9-IO-222R2-A: 6.8 W, maximum BB-ZXT24-IO-222R2: 4.5 W, maximum

DIGITAL INPUTS	
Voltage Range, Configuration	0 – 48 VDC PNP (default) / NPN (selectable)
Low Voltage (0)	1 VDC maximum
High Voltage (1)	Greater than 1 VDC
Pull Up/Down Current	38 µA
Frequency Input	2 DI per module, software selectable as counters with 0 to 20 KHz range
DIGITAL OUTPUTS (RELAY)	
Number of Relays	2
Type	C (Normally Open and Normally Closed)
Output	3 Terminals per relay (Common, NO, NC)
Communication	3.5 mm Terminal Block
Ratings	250 VAC @ 4 A, 30 VDC @ 4 A
ANALOG INPUTS / OUTPUTS	
Ranges	0 – 5 VDC, 0 – 10 VDC, 0 – 20 mA, 4 – 20 mA
Resolution	16-bit (Inputs), 12-bit (outputs)
AI Load Resistance	100 MΩ – configured for Voltage 250 Ω – configured for Current
AO Output Current	1 mA maximum, configured for Voltage
AO Source Load	450 Ω maximum, configured for current
Input Protection	Over-voltage to 2x maximum input voltage
TERMINAL BLOCKS	
Wire Size	26 – 4 AWG
Torque	0.5 Nm (minimum), 0.6 Nm maximum
ENVIRONMENT	
Dimensions	13.01 x 13.01 x 6.02 cm (5.12 x 5.12 x 2.37 in)
Operating Temperature	-40 to +74 °C (-40 to +165 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Operating Humidity	0 – 95% (non-condensing)
Enclosure Rating	IP67
Use	Indoor and Outdoor
MEANTIME BETWEEN FAILURE (MTBF) - MIL 217F	
MTBF	BB-ZXT9-IO-222R2-A: 386969 hours BB-ZXT24-IO-222R2: 383331 hours
REGULATORY, APPROVALS, DIRECTIVES, STANDARDS	
CE (BB-ZXT24-IO-222R2 only) FCC Part 15 GFR Title 47 – Digital Apparatus (Federal Communications Commission) ICES-003 Class B – Digital Apparatus (Industry Canada)	
EMC:	ETSI EN 301 489-1 v1.9.2 ETSI EN 301 489-1 v2.2.1 Applied in accordance with the specific requirements of EMC and Radio Spectrum Matters: Broadband Data Systems EN 55032 Class B – Electromagnetic Compatibility of Multimedia Equipment – emission requirements EN 61000-6-3 + A1 – Generic Emission Standard for Residential, Commercial and Light-industrial Environments EN 61000-6-2 – Generic Immunity Standard for (heavy) Industrial Environments
CE (BB-ZXT24-IO-222R2 only)	SAFETY: EN 60950-1 +A11 +A1 +A12 +A2 - Information Technology Equipment – Safety - Part 1: General Requirements EN 62479 – RF Exposure Limits
ENVIRONMENTAL:	IEC 60068-2-6 – Vibration, 10-500 Hz, 4G, 3 axes IEC-60068-2-27 – Shock, 50G peak, 3 axes IEC-60068-2-32 – Drop, 10 total drops from 1 meter, from sides, edges and corner
UL	C1/D2, File E245458