

# IPC-6025

## 5-Slot Desktop/Wallmount Chassis with Scalability as 5U Quad-System Solution




### Features

- Front handle for easy withdraw in rackmount carrier
- Lockable front door prevents unauthorized access
- Shockproof drive bay for two 3.5" HDDs
- LED indicators for system fault detection
- Optional rackmount carrier for quad-system solution
- Built-in Intelligent System Module enabling whole system fan control and remote manageability


### Specifications

Drive Bay		External	Internal
	3.5"	1	1
Cooling	Fan	1 (9 cm / 46.6 CFM)	
	Air Filters	Yes	
Front I/O Interface	USB 2.0	2	
Miscellaneous	LED Indicators	Power, fan, temperature, HDD	
	Control	Power switch and system reset buttons	
	Rear Panel	Reserved Two 9-pin D-Sub openings	
Intelligent System Module Remote Monitoring	CPU/System fan speed , CPU/System temperature , motherboard voltage (Only selected Advantech MBs/CPU cards with WISE-PaaS/RMM installed can fully enable these functions, check with Advantech local rep. for detailed information.)		
Environment		Operating	Non-operating
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)
	Humidity	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms	2 G
	Shock	10 G (with 11 ms duration, half sine wave)	
Physical Characteristics	Dimensions (W x H x D)	111 x 212 x 420 mm (4.4" x 8.3" x 16.5")	
	Weight	4.7 kg (10.3 lb)	

### Front View



### Rear View





Note: Hot swap drive bay module should be bought separately.

4 IPC-6025 combined as a 5U quad-system rackmount IPC





Technical drawings of the 19-inch rackmount server showing front, side, and rear views with dimensions:

- Front View:** Shows the front panel with a handle on the left and a small rectangular display or indicator on the right. Dimensions: 420 [16.54] (width), 212 [8.35] (height).
- Side View:** Shows the side profile of the server. Dimensions: 111.0 [4.37] (depth).
- Rear View:** Shows the rear panel with multiple ports and connectors. Dimensions: 445.5 [17.54] (width).

### Single System



## Quad System



Part number	Power Supply	80 Plus Grade	Wattage	Type	Input	Switch type
IPC-6025BP-27ZE	96PS-A270WFX	White	270W	Single	AC 100 ~ 240V (Full Range )	ATX Switch
IPC-6025BP-40ZE	96PS-A400WFX-2	Gold	400W	Single	AC 100 ~ 240V (Full Range)	ATX Switch

Ordering P/N	Description
9892602501E	Rackmount carrier for Quad System solution
IPC-DT-3120E	Mobile rack for dual 2.5" SATA HDDs

Model	PICMG 1.3/1.0	PCIe	PCI-X	PCI	ISA	PCI/ISA
<b>PCE-5000 Series</b>						
PCE-5B04-20B1E	PICMG 1.3	1 (PCIe x 16)	2	-	-	-
PCE-5B05-02A1E	PICMG 1.3	1 (PCIe x 16) 1 (PCIe x 4)	-	2	-	-
PCE-5B05-03A1E	PICMG 1.3	1 (PCIe x 16)	-	3	-	-
<b>PICMG 1.0</b>						
PCA-610SP3-5A1E	PICMG 1.0	-	-	2	1	1