



**CS2050G-M**

- Complies with IEEE802.3, IEEE802.3u standards;
- 5 10/100/1000Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX;
- Supports IEEE802.3x flow control for Full Duplex mode and backpressure for half-duplex mode;
- Supports MAC address auto-learning and auto-aging;
- LED indicators for monitoring power, link, activity;
- External Power adapter 5VDC/1A;
- Dimension: 92\*68\*25mm.

## Brief Views

The Fast Ethernet Switch provides 5 10/100/1000Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. The Switch is Plug-and-Play and each port can be used as general ports or Uplink ports and can be simply plugged into a server, a hub or a switch, using straight cable or crossover cable.

## Specification

<b>Interface</b>	5 10/100/1000/Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
<b>Power</b>	Input: 5VDC /1A
<b>Transfer Method</b>	Store and Forward
<b>Advanced Functions</b>	Green Technology, saving power up to70% 802.3X Flow Control, Back Pressure Auto-Uplink Every Port
<b>Package Contents</b>	5-Port 10/100/1000Mbps Desktop Switch Power Adapter User Guide
<b>Environment</b>	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing