

CE<sup>2.0</sup>

NEW



## MSW-202A

2x GbE/RJ45 + 2x 1G/SFP  
L2+ Carrier Ethernet Switch (EDD)

MSW-202A is a carrier class Ethernet Demarcation Device (EDD) with 2x 10/100/1000Base-T Ethernet ports and 2 x 100/1000/2500Base-X triple rate SFP fiber ports which enables E-Line & E-Access services with advanced carrier Ethernet features per CE2.0. By supporting link and service Ethernet OAM schemes, the MSW-202A also provides extensive fault detection and diagnostic capabilities to ensure that actual network use complies with pre-agreed service level agreements (SLAs).

## Features


- Complies with CE2.0 (E-Line / E-Access)
- IPv6 management
- IEEE 802.3ah, IEEE 802.1ag, ITU-T Y.1731
- IEEE 1588v2

## Specifications

Interface	100/1000Mbps SFP slots x 2 + 10/100/1000Base-T RJ45 x 2
Filter & Forward rate	14880pps at 10Mbps, 148800pps at 100Mbps, 1488000pps at 1Gbps
Switching Fabric Capacity	8Gbps
Transmission Method	Store and Forward Switching
Standard	IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1ad, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1x, IEEE 802.3ad, IEEE802.3ah, IEEE802.1ag, IEEE 802.3az, ITU-T Y.1731, ITU-T G.8031, ITU-T G.8032
Packet Buffer	4M bits
MAC Table Size	8K
Max. Packet Size	9.6K Bytes
VLAN Feature	IEEE 802.1Q tagged VLAN(Max. 4K VLAN groups), port based VLAN, MAC based VLAN, protocol based VLAN, private VLAN, IEEE 802.1ad Q-in-Q, VLAN translation, GVRP
QoS Feature	IEEE 802.1p 8 priority queues per port, CoS based on switch port; VLAN ID; DSCP; TCP/UDP port, IEEE 802.1p priority tag remarking, DSCP remarking, Port based ingress/egress rate limit, 3 colors marker-CIR/EIR/Burst bandwidth control
L2 switching protection	STP, RSTP, MSTP, ITU-T G.8031/G.8032 Ethernet ring protection
Trunking	IEEE 802.3ad LACP(Max. 2 trunking groups, Max. 4 ports per trunking group)
Security	IEEE 802.1x port based access control, MAC based access control authentication, RADIUS authentication, limited MAC address learning, IP/MAC binding, ACL rule based filtering, TACACS+, IP source guard, DHCP snooping/relay option 82, ARP inspection

IP Multicasting	IGMP throttling, IGMP filtering, IGMP fast leave, IGMP snooping v1/v2/v3, MVR, MLD snooping v1/v2
Storm Control	Unknown Unicast/Broadcast/Multicast storm suppression
Management	Web/Telnet CLI/SNMP/console interface, Web/CLI authentication, SSH v2, HTTPs, port mirroring, syslog, IPv6 management, NTP, IEEE 802.3az, Energy, Efficient, Ethernet (EEE) power management
SNMP Agent	SNMP v1/v2c/v3, RMON Group 1,2,3 and 9
Software Upgrade	TFTP/HTTP
Ethernet OAM	IEEE 802.3ah, IEEE 802.1ag, ITU-T Y.1731
Timing Synchronization	IEEE 1588v2
LED Display	Power, System, Console, Link, Speed/Act
Power Input	100V ~ 240VAC, -18 ~ -75VDC
Power Consumption	< 12W
Operating Temperature	0 ~ 50°C
Storage Temperature	-25 ~ 70°C
Humidity	5% ~ 90% (non-condensing)
Dimensions	201 x 135 x 35 mm (D x W x H) (with CH01M Chassis)
Regulatory	FCC, CE

## Application



## Ordering Information

Model Name	Description
MSW-202A-AC	2x SFP Slots in Dual Rate 100/1000Base-X and 2x 10/100/1000Base-T RJ45 OAM Managed Carrier Ethernet Switch with single AC power supply
MSW-202A-DC	2x SFP Slots in Dual Rate 100/1000Base-X and 2x 10/100/1000Base-T RJ45 OAM Managed Carrier Ethernet Switch with single DC power supply
MSW-202A-AD	2x SFP Slots in Dual Rate 100/1000Base-X and 2x 10/100/1000Base-T RJ45 OAM Managed Carrier Ethernet Switch with AC & DC power supply

Power Type

MSW - 202A - ☐

Example: MSW - 202A - AC