



TGAR-1062+-4G6S-M12

**Industrial EN50155 IEEE 802.11 a/b/g/n 4G LTE Cellular Router
With 2x10/100/1000Base-T(X), 1-port PoE P.D, M12 connector**

Features

- Leading EN50155-compliant wireless access point for rolling stock application
- High Speed Air Connectivity: WLAN interface support up to 300Mbps link speed
- Highly Security Capability: WEP/WPA/WPA-PSK(TKIP,AES)/WPA2/WPA2-PSK(TKIP,AES)/802.1X Authentication supported
- Secured Management by HTTPs
- Various kind of WAN Connection Type supported: Dynamic/Static IP, PPPoE, Modem Dial Up
- IP table configurable to prevent access from unauthorized IP address
- Support VPN for secured network connection (Open VPN , PPTP VPN)
- Support NAT Setting (Virtual Server , Port Trigger , DMZ , UPnP)
- Support DHCP forwarding through PPTP function
- Category 6 LTE Modem dial up included
- GPS support for GPS model.
- 1KV isolation for PoE P.D. port
- Event Warning by Syslog, Email, SNMP Trap and Relay output
- Ultra rugged enclosure for toughest industrial usages
- Wall mounting enabled



Introduction

ORing's Transporter™ series cellular router is designed for industrial and rolling stock wireless applications, such as vehicle, and railway applications. TGAR-1062+-4G6S-M12 is reliable IEEE802.11 a/b/g/n router with 2 ports LAN which is fully compliant with EN50155 certification. It could be configured to operate in 3 modes of routing function: Dynamic/Static IP route, PPPoE authentication, and Cellular modem dial up. Users can set up WLAN environment to fulfill demands of various applications rapidly by dialing up cellular modem. TGAR-1062+-4G6S-M12 EN50155 cellular VPN router use M-series connectors to ensure tight, robust connections, and guarantee reliable operation against environmental disturbances, such as vibration and shock. In addition, TGAR-1062+-4G6S-M12 also provides P.D. feature on ETH2 which is fully compliant with IEEE802.3af PoE P.D. specification and TGAR-1062+-4GS-M12 supports GPS function. Therefore, TGAR-1062+-4G6S-M12 is one of the most reliable choices for rolling stock applications on the wireless network.

Application


In TGAR-1062+-4G6S-M12 , there are 3 modes of routing functions supported: Dynamic/Static IP route, PPPoE dial up, and Modem dial up. TGAR-1062+-4G6S-M12 also support NAT, VPN and Back up functions. You can build up the wireless network and connect to the Internet easily.

Pin Definition

Relay Output



Console




DI




DO



Power




Ethernet



- 1 BI_DC+
- 2 BI_DD+
- 3 BI_DD-
- 4 BI_DA-
- 5 BI_DB+
- 6 BI_DA+
- 7 BI_DC-
- 8 BI_DB-

Dimension



Specifications

ORing EN50155 WLAN Access Point Router Model	TGAR-1062+4G-M12
Physical Ports	
10/100/1000Base-T(X) Ports in M12 Auto MDI/MDIX (8-pin A-coding)	2 (Present at ETH2 Fully compliant with IEEE 802.3af PoE P.D)
DIDO port in M12 (5-pin A-coding)	2(DI x 4 and DO x 4) : Dry Contact: On: short to GND, Off: open Wet Contact (DI to COM/GND): On: 0 to 3VDC, Off: 10 to 30VDC
RS-232 Console port in M12 (5-pin A-coding)	115200, 8 ,N ,1
Relay port in M12 (5-pin A-coding)	1A@24VDC
SIM Card Slot	1 (Mini SIM only without adapter)
GPS (-4GS model only)	
Antenna Connector	1 x External reverse SMA antenna connector
Frequency	1575.42MHz
WLAN Interface	
Antenna Connector	2 x Reverse SMA Female
Radio Frequency Type	DSSS, OFDM
Modulation	IEEE802.11a : OFDM with BPSK, QPSK, QAM, 64QAM IEEE802.11b: CCK, DQPSK, DBPSK IEEE802.11g: OFDM with BPSK, QPSK, 16QAM, 64QAM IEEE802.11n : BPSK, QPSK, 16-QAM, 64-QAM
Frequency Band	America / FCC : 2.412~2.462 GHz (11 channels) 5.180~5.240 GHz & 5.745~5.825 GHz (9 channels) Europe CE / ETSI : 2.412~2.472 Ghz (13 channels) 5.180~5.240 GHz (4 channels)
Transmission Rate	IEEE802.11b: 1 / 2 / 5.5 / 11 Mbps IEEE802.11a/g: 6 / 9 / 12 / 18 / 24 / 36 / 48 / 54 Mbps IEEE801.11n: up to 300Mbps
Transmit Power	802.11a: 12dBm ± 1.5dBm@54Mbps 802.11b: 17dBm ± 1.5dBm@11Mbps 802.11g: 16dBm ± 1.5dBm@54Mbps 802.11gn HT20: 15dBm ± 1.5dBm @MCS7 802.11gn HT40: 14dBm ± 1.5dBm @MCS7 802.11an HT20: 12dBm ± 1.5dBm @MCS7 802.11an HT40: 11dBm ± 1.5dBm @MCS7
Receiver Sensitivity	802.11a : -76dBm ± 2dBm@54Mbps 802.11b : -85dBm ± 2dBm@11Mbps 802.11g : -76dBm ± 2dBm@54Mbps 802.11gn HT20:-75dBm ± 2dBm@MCS7 802.11gn HT40:-72dBm ± 2dBm@MCS7 802.11an HT20:-74dBm ± 2dBm@MCS7 802.11an HT40:-71dBm ± 2dBm@MCS7
Encryption Security	WEP: (64-bit ,128-bit key supported) WPA/WPA2 :802.11i(WEP and AES encryption) WPAPSK (256-bit key pre-shared key supported) 802.1X Authentication supported TKIP encryption
Wireless Security	SSID broadcast disable
Cellular Interface	
Cellular Standard	GSM / GPRS/ EGPRS/ EDGE / WCDMA / HSDPA / HSUPA /HSPA+ /LTE
Antenna Connector	2 x SMA Female
Band Option	Asia/Australia LTE: FDD:B1/B3/B5/B7/B8/B18/B19/B21/B28 Band

	<p>TDD:B38/B39/B40/B41 Band</p> <p>TD-SCDMA: B39 Band</p> <p>UMTS/HSDPA/HSUPA/HSPA+/DC-HSPA+: B1/B5/B6/B8/B9/B19 Band</p> <p>American/Europe</p> <p>LTE: FDD:B1/B2/B3/B4/B5/B7/B8/B12/B13/B20/B25/B26/B29/B30 Band TDD:B41 Band</p> <p>UMTS/HSDPA/HSUPA/HSPA+/DC-HSPA+: B1/B2/B3/B4/B5/B8 Band</p>
Protocol Support	
Protocol	ARP,BOOTP, DHCP, DNS, HTTP, IP, ICMP, SNTP, TCP, UDP, RADIUS, SNMP, PPPoE
LED Indicators	
Power Indicator	<p>2 x LEDs,</p> <p>PW1:Green for DC Power on</p> <p>PW2:Green for DC Power on or power by PoE</p>
10/100/1000Base-T(X) port Indicator	2 x LEDs, Green for port Link/Act
WLAN LED	1 x LED, Green for WLAN Link/Act
WAN LED	1 x LED, Green for functioning normal
Fault Indicator	1 x LED, Red for Ethernet link down or power down indicator
Fault Contact	
Relay	Relay output to carry capacity of 3A at 24VDC
Power	
Redundant Input Power	Dual Power Inputs with M23 connector. Nominal 24/48Vdc(12~48Vdc)
Power Consumption (Typ.)	10.5Watts
Overload Current Protection	Present
Reverse Polarity Protection	Present
Physical Characteristic	
Enclosure	IP-40
Dimension (W x D x H)	125.6(W) x 65(D) x 196.1(H) mm (4.94 x 2.55 x 7.72 inch.)
Weight (g)	980g
Environmental	
Storage Temperature	-40 to 85°C (-40 to 185°F)
Operating Temperature	-25 to 70°C (-13 to 158°F)
Operating Humidity	5% to 95% Non-condensing
Regulatory Approvals	
EMI	FCC Part 15, CISPR (EN55022) class A, EN50155 (EN50121-3-2)
EMS	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
Shock	IEC60068-2-27, EN61373
Free Fall	IEC60068-2-31
Vibration	IEC60068-2-6, EN61373
Rail Traffic	EN50155
Cooling	EN60068-2-1
Dry Heat	EN60068-2-2
Safety	EN60950-1
Warranty	5 years

Ordering Information

TGAR-ABCDE-FFFG-M12

Code Definition	Cellular Module Number	2 nd Wireless Mode	1 st Wireless Mode	Giga Ethernet Port Number	PoE Identification	Cellular Generation / Category	GPS Function
Option	1: One	1: 802.11 b/g	1: 802.11 b/g	2: 2 ports	-"+": PoE P.D.	4G :LTE	S:GPS
	2: Dual	2: 802.11 a	2: 802.11 a		present at	under	
		3: 802.11 a/b/g	3: 802.11 a/b/g		ETH2	Category 6	
		4: 802.11 b/g/n	4: 802.11 b/g/n			4G6:LTE	
		5: 802.11 a/n	5: 802.11 a/n			Category 6	
		6: 802.11 a/b/g/n	6: 802.11 a/b/g/n				

	Model Name	Description
Available Model	TGAR-1062+-4G6S-M12_US	Industrial EN50155 IEEE 802.11 a/b/g/n 4G LTE Cellular Router With 2x10/100/1000Base-T(X), 1-port PoE P.D, M12 connector, US Band
	TGAR-1062+-4G6S-M12_EU	Industrial EN50155 IEEE 802.11 a/b/g/n 4G LTE Cellular Router With 2x10/100/1000Base-T(X), 1-port PoE P.D, M12 connector, EU Band
	TGAR-1062+-4G6S-M12_CN	Industrial EN50155 IEEE 802.11 a/b/g/n 4G LTE Cellular Router With 2x10/100/1000Base-T(X), 1-port PoE P.D, M12 connector, CN Band
	TGAR-1062+-4G6S-M12_TW	Industrial EN50155 IEEE 802.11 a/b/g/n 4G LTE Cellular Router With 2x10/100/1000Base-T(X), 1-port PoE P.D, M12 connector, TW Band

Packing List

- TGAR-1062+-4G6S-M12 x 1
- CD x 1
- Quick Installation Guide x 1
- 2.4GHz/5GHz Antenna x 2
- LTE Antenna x 2

Optional Accessories

- DR-45 series : 45 Watts power supply
- DR-75 series : 75 Watts power supply
- DR-120 series : 120 Watts power supply
- WLAN RF Antenna series
- RF Antenna Base series
- RF Cable series